

Patchcord CAT6A F/UTP RJ45 LSZH

P/N: LAT-CAT6AF-XX-XX

DESCRIPTION AND CHARACTERISTICS

Category 6A Ethernet patch cord with RJ-45 male connectors with injected boots.

Available in grey, yellow, green, blue, red, orange, violet, pink, black and white colors.

Available in lengths of 0.15 / 0.3 / 0.5 / 1 / 1.5 / 2 / 3 / 5 / 7.5 / 10 / 15 / 20 / 25 meters.



SPECIFICATIONS:

CONNECTOR A:	RJ-45 Shielded
CONNECTOR B:	RJ-45 Shielded
SHIELDING:	F/UTP
JACKET:	Halogen free, low smoke LSZH/LSOH
OUTER DIAMETER:	5mm
CONDUCTOR:	Solid copper
AWG:	AWG 26/7
COLOR CODE:	ANSI/EIA/TIA 568 & ISO/IEC 11801
FREQUENCY:	500 MHz
TRANSMISSION SPEED:	10Gb
IMPEDANCE:	100 Ω

Patchcord CAT6A F/UTP RJ45 LSZH

PART NUMBERS

	GREY	WHITE	BLACK	RED	BLUE
0,15 m	LAT-CAT6AF-GR-0.15	LAT-CAT6AF-BL-0.15	LAT-CAT6AF-NG-0.15	LAT-CAT6AF-RJ-0.15	LAT-CAT6AF-AZ-0.15
0,3 m	LAT-CAT6AF-GR-0.3	LAT-CAT6AF-BL-0.3	LAT-CAT6AF-NG-0.3	LAT-CAT6AF-RJ-0.3	LAT-CAT6AF-AZ-0.3
0,5 m	LAT-CAT6AF-GR-0.5	LAT-CAT6AF-BL-0.5	LAT-CAT6AF-NG-0.5	LAT-CAT6AF-RJ-0.5	LAT-CAT6AF-AZ-0.5
1 m	LAT-CAT6AF-GR-1	LAT-CAT6AF-BL-1	LAT-CAT6AF-NG-1	LAT-CAT6AF-RJ-1	LAT-CAT6AF-AZ-1
1,5 m	LAT-CAT6AF-GR-1.5	LAT-CAT6AF-BL-1.5	LAT-CAT6AF-NG-1.5	LAT-CAT6AF-RJ-1.5	LAT-CAT6AF-AZ-1.5
2 m	LAT-CAT6AF-GR-2	LAT-CAT6AF-BL-2	LAT-CAT6AF-NG-2	LAT-CAT6AF-RJ-2	LAT-CAT6AF-AZ-2
3 m	LAT-CAT6AF-GR-3	LAT-CAT6AF-BL-3	LAT-CAT6AF-NG-3	LAT-CAT6AF-RJ-3	LAT-CAT6AF-AZ-3
5 m	LAT-CAT6AF-GR-5	LAT-CAT6AF-BL-5	LAT-CAT6AF-NG-5	LAT-CAT6AF-RJ-5	LAT-CAT6AF-AZ-5
7,5 m	LAT-CAT6AF-GR-7.5	LAT-CAT6AF-BL-7.5	LAT-CAT6AF-NG-7.5	LAT-CAT6AF-RJ-7.5	LAT-CAT6AF-AZ-7.5
10 m	LAT-CAT6AF-GR-10	LAT-CAT6AF-BL-10	LAT-CAT6AF-NG-10	LAT-CAT6AF-RJ-10	LAT-CAT6AF-AZ-10
15 m	LAT-CAT6AF-GR-15	LAT-CAT6AF-BL-15	LAT-CAT6AF-NG-15	LAT-CAT6AF-RJ-15	LAT-CAT6AF-AZ-15
20 m	LAT-CAT6AF-GR-20	LAT-CAT6AF-BL-20	LAT-CAT6AF-NG-20	LAT-CAT6AF-RJ-20	LAT-CAT6AF-AZ-20
25 m	LAT-CAT6AF-GR-25	LAT-CAT6AF-BL-25	LAT-CAT6AF-NG-25	LAT-CAT6AF-RJ-25	LAT-CAT6AF-AZ-25

	GREEN	YELLOW	ORANGE	VIOLET	PINK
0,15 m	LAT-CAT6AF-VD-0.15	LAT-CAT6AF-AM-0.15	LAT-CAT6AF-NJ-0.15	LAT-CAT6AF-VL-0.15	LAT-CAT6AF-RS-0.15
0,3 m	LAT-CAT6AF-VD-0.3	LAT-CAT6AF-AM-0.3	LAT-CAT6AF-NJ-0.3	LAT-CAT6AF-VL-0.3	LAT-CAT6AF-RS-0.3
0,5 m	LAT-CAT6AF-VD-0.5	LAT-CAT6AF-AM-0.5	LAT-CAT6AF-NJ-0.5	LAT-CAT6AF-VL-0.5	LAT-CAT6AF-RS-0.5
1 m	LAT-CAT6AF-VD-1	LAT-CAT6AF-AM-1	LAT-CAT6AF-NJ-1	LAT-CAT6AF-VL-1	LAT-CAT6AF-RS-1
1,5 m	LAT-CAT6AF-VD-1.5	LAT-CAT6AF-AM-1.5	LAT-CAT6AF-NJ-1.5	LAT-CAT6AF-VL-1.5	LAT-CAT6AF-RS-1.5
2 m	LAT-CAT6AF-VD-2	LAT-CAT6AF-AM-2	LAT-CAT6AF-NJ-2	LAT-CAT6AF-VL-2	LAT-CAT6AF-RS-2
3 m	LAT-CAT6AF-VD-3	LAT-CAT6AF-AM-3	LAT-CAT6AF-NJ-3	LAT-CAT6AF-VL-3	LAT-CAT6AF-RS-3
5 m	LAT-CAT6AF-VD-5	LAT-CAT6AF-AM-5	LAT-CAT6AF-NJ-5	LAT-CAT6AF-VL-5	LAT-CAT6AF-RS-5
7,5 m	LAT-CAT6AF-VD-7.5	LAT-CAT6AF-AM-7.5	LAT-CAT6AF-NJ-7.5	LAT-CAT6AF-VL-7.5	LAT-CAT6AF-RS-7.5
10 m	LAT-CAT6AF-VD-10	LAT-CAT6AF-AM-10	LAT-CAT6AF-NJ-10	LAT-CAT6AF-VL-10	LAT-CAT6AF-RS-10
15 m	LAT-CAT6AF-VD-15	LAT-CAT6AF-AM-15	LAT-CAT6AF-NJ-15	LAT-CAT6AF-VL-15	LAT-CAT6AF-RS-15
20 m	LAT-CAT6AF-VD-20	LAT-CAT6AF-AM-20	LAT-CAT6AF-NJ-20	LAT-CAT6AF-VL-20	LAT-CAT6AF-RS-20
25 m	LAT-CAT6AF-VD-25	LAT-CAT6AF-AM-25	LAT-CAT6AF-NJ-25	LAT-CAT6AF-VL-25	LAT-CAT6AF-RS-25